



TECHNICAL INFORMATION

1. BEARING LUBRICATION DE: CHEVRON SRI
ODE: CHEVRON SRI
2. BEARING TYPE DE: 6322C3
ODE: 6322C3 INSULATED
3. WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(Pt0°C-100ohm)
LOCATION: IN STATOR SLOT
4. BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
5. SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 200
6. ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS BI DIRECTIONAL
7. MOTOR PAINT COLOR: GRAY
8. APPROX. WEIGHT: 7000 Lbs
9. ACCESORIES: _____

UNITS: INCHES

DRAWING LIST		MOTOR OUTLINE FOR THREE PHASE INDUCTION MOTOR									
MAIN TERMINAL BOX 130-7622-55		CUSTOMER NAME			P.O. NO.		MOTOR TAG NO.				
AUX TERMINAL BOX FOR		OUTPUT HP	POLE	VOLTAGE	FREQUENCY	FULL LOAD SPEED		TOSHIBA MODEL NO.			
SPACE HEATER	130-7520-50	2	4-8	V	Hz	(min ⁻¹)					
R.T.D.	130-7522-51	TYPE	FORM	INS. CLASS	RATING	FRAME		S.F.	ENCLOSURE		
THERMISTOR	N/A			F	CONT.	5809/10/11US			TEFC		
		TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.									
PRODUCTION #	N/A	3rd ANGLE PROJ.	PREPARED BY:	DATE:	CHECKED BY:	DATE:	DRAWING NO.:	REV.			
			B SIDLE	8/2/06	D.LAJINESS	8/4/06	MDSL0071-18	2			
NO.	REVISION	BY	DATE								

2	ADD CI FANCOVER	BCS	4/24/07
1	ADD SH & RTD AUX BOX	BCS	9/13/06
0	FIRST ISSUE	BCS	8/2/06